



The most advance and precise pad printer ever built



Auto pad clean

OPTIONAL



Antistatic blower



Product holding in/out shuttle

FEATURES

- Servo drive pad printer
- High speed machine design: pad moves up/down, printing plate moves in/out
- Powerful motor to maximize pad selection
- Heavy-duty STAR Ball screws
- Precision guide rails with runner-blocks
- Extended pad guide rails that ensure pad stroke stability when printing below base
- Programmable pad stroke
- Programmable printing plate position
- Time delay settings for ideal ink release
- Dual-speed pad movement
- Easy ink cup load/unload, no pad remove need
- Auto pad clean with programmable clean cycle
- KENT patented sealed ink cup system
- Zero adjustment, dead on printing plate registration for fast job change
- PLC control, touch screen interface

SPECIFICATIONS

Ink cup size :	Ø90 mm
Plate size :	100 x 250 mm
Speed : (dry cycle)*	1,500/hr.
Pad compression :	400W servo motor
Pad carriage stroke (in/out) :	138 mm
Power :	220V 2KW
Air consumption :	40 L/min.
Accuracy :	+/- 0.02 mm
Repeatability :	+/- 0.02 mm
Size (LxWxH) :	1,150 x 700 x 1,810 mm
Weight :	220 kg (approx.)

* Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.