



AVC - Automatic Viscosity Control (patented)



2-Station PNEUMATIC Turntable

FEATURES

- A high speed, user-friendly pad printer
- Productivity is doubled with the 2-Station Turntable; print at one station while load/unload at the other
- Automatic pad clean
- Pneumatic turntable
- Pneumatic pad stroke
- APS: Automatic pad stroke by optical scale
- THK linear guide rail with runner blocks
- Use **Green ink cup** (patented) set up
- Powered with AVC - Automatic Viscosity Control (patented)
- Compatible with long life, economy of **Green plate**, 10 mm steel plate and thin steel plate
- Dead-on printing plate registration for quick job change
- CE European safety standard

SPECIFICATIONS

Ink cup size :	Ø90 mm
Plate size :	100 x 250 mm
Pad stroke :	0-150 mm (optional 200 mm)
Max. pad pressure :	480N at 6 bar
Speed : *	4,000 cycles/hr.
Turntable size :	Ø280 mm
Index stations :	2
No. of fixtures :	2
Power :	110/220V 50/60Hz 30W
Air consumption :	336 litre/min.
Size : L x W x H	820 x 624 x 1,420 mm
Weight :	125 Kg (Approx.)

* Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.

