

KENT PP21N-PPS/2



AVC - Automatic Viscosity Control (patented)

OPTIONAL



User-friendly: Steering up/down work table



Pneumatic pad shuttle



Newly improved MS-100 machine stand enhances stability

FEATURES

- 2 color automatic pad printer
- Pneumatic pad shuttle system (PPS)
- Rigid aluminium casting machine frame
- Use Green ink cup (patented) set up
- Powered with AVC - Automatic Viscosity control (patented)
- Compatible with long life, economy of Green plate, thin steel plate and 10 mm steel plate
- Dead-on printing plate registration for quick job change
- Membrane switch control panel
- Automatic pad clean with programmable cleaning cycle
- Special functions: double ink / print cycles, dwell and delay before print
- Hardened ground steel shaft with impregnated bushing ensure friction-free movement
- High speed and smooth machine operations

SPECIFICATIONS

Ink cup :	Ø60, 70, 90 mm x 2
Ink cup plate size :	100 x 250 mm x 2
Max. speed : (dry cycle) *	850 cycles/hr.
Max. pad pressure :	750N at 6 bar
Power :	110/220V 50/60Hz 20W
Air consumption :	71 litre/min. (approx.)
Size : (LxWxH)	790 x 810 x 570 mm
Weight :	90 kg (approx.)

* Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.



www.kentpp.com

121M-0419

KENT ENGINEERING CO., LTD.

(Hong Kong) Tel: 852-2424 1899 Email: info@kent.com.hk

KENT ENGINEERING (GAO YAO) CO., LTD.

(Zhaoqing) Tel: 0758-8512 888 Email: kentgy@kentchina.com
 (Dongguan) Tel: 0769-8777 2010 Email: kentsg@kentchina.com
 (Wuxi) Tel: 0510-8522 0330 Email: kentsh@kent-pp.com.cn
 (Tianjin) Tel: 022-2795 8926 Email: kenttj@kent-pp.com.cn

