

2 color pad printer (with sealed ink cup)



AVC - Automatic Viscosity Control (patented)



Automatic Pad Clean



2 color pneumatic shuttle

OPTIONAL



Newly improved MS-100 machine stand enhances stability

FEATURES

- 2 color automatic pad printer
- Rigid aluminium casting machine frame
- 2 color pneumatic shuttle
- Use **Green ink cup** (patented) set up
- Powered with AVC - Automatic Viscosity Control (patented)
- Compatible with long life, economy of **Green plate**, 10 mm steel plate and thin steel plate
- Dead-on printing plate registration for quick job change
- Membrane switch control panel
- Automatic pad clean with programmable cleaning cycle
- Special functions: double ink / print cycles, dwell and delay before print
- Digital pad stroke (DPS) for variable printing depth
- Hardened ground steel shaft with impregnated bushing ensure friction-free movement
- High speed and smooth machine operations

SPECIFICATIONS

| | |
|----------------------------|--------------------------|
| Ink cup : | Ø60, 70, 90 mm |
| Max. speed : (dry cycle) * | 850 cycles/hr. |
| Max. pad pressure : | 750N at 6 bar |
| Power : | 110/220V 50/60Hz 20W |
| Air consumption : | 128 litre/min. (approx.) |
| Size : L x W x H | 750 x 655 x 570 mm |
| Weight : | 62 Kg (approx.) |

*Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.

