

Versatile Pad Printer in the Market



High speed digital shuttle: 1,200 mm/sec



Quick job change



Ideal for promotion and industrial products



(Samples for reference only)

FEATURES

- 4-color printer designed for frequent job changes
- Rigid aluminium casting machine frame
- Servo motor drive digital shuttle coupled with "STAR" lead-screw and THK linear guide-rail.
- Digital shuttle speed: 1,200 mm/sec.
- Digital shuttle repeatability: +/- 0.02 mm
- Use **Green ink cup** set up (patented)
- Compatible with long life, economy of **Green plate**, 10 mm steel plate and thin steel plate
- Dead-on printing plate registration for quick job change in 3 minutes
- Membrane switch control panel
- Only one jig need
- Automatic pad clean with programmable cleaning cycle
- Special functions: double ink / print cycles, dwell and delay before print
- Digital pad stroke (DPS) for variable printing depth
- Hardened ground steel shaft with impregnated bushing ensure friction-free movement
- High speed and smooth machine operations

SPECIFICATIONS

| | |
|---------------------------|----------------------------|
| Ink cup: | Ø 90 mm x 4 |
| Plate size: | 100 x 250 mm |
| Max. speed: (dry cycle) * | 570 Cycles / Hr. |
| Max. pad pressure: | 1,870N at 6 Bar |
| Power: | 220VAC, 50/60Hz, 430W |
| Air consumption: | 230 Litre / Min. (Approx.) |
| Size: L x W x H | 1,081 x 1,182 x 1,580 mm |
| Weight: | 220 Kg (Approx.) |

* Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.



www.kentpp.com

123M-0223

KENT ENGINEERING CO., LTD.

(Hong Kong) Tel: 852-2424 1899 Email: info@kent.com.hk

KENT ENGINEERING (GAO YAO) CO., LTD.

(Zhaoqing) Tel: 0758-8512 888 Email: kentgy@kentchina.com
 (Dongguan) Tel: 0769-8777 2010 Email: kentsg@kentchina.com
 (Wuxi) Tel: 0510-8522 0330 Email: kentsh@kent-pp.com.cn
 (Tianjin) Tel: 022-2795 8926 Email: kenttj@kent-pp.com.cn

