



PLC control touch screen panel



Motor drive auto pad clean



Max work space
(Pad clean underneath)

FEATURES

- Single color automatic pad printer
- PLC control touch screen panel
- Automatic pad clean with programmable cleaning cycle
- Rigid aluminium cast machine frame
- Platform in/out movement
- Pneumatic power machine operation
- Use **Green ink cup** (patented) set up
- Able to use laser engraved **Green plate**, thin steel plate, 10 mm steel plate and polymer plate
- Dead-on printing plate registration for quick job change
- Pad stroke & speed adjustment
- Special functions: double ink / print cycles, dwell (delay after print / after ink), delay before print / before ink
- Digital pad stroke (DPS) for variable printing depth
- Hardened ground steel shaft with impregnated bushing ensure friction-free movement
- High speed and smooth machine operations
- CE standard

SPECIFICATIONS

Ink cup size : (mm)	Ø90 (Ø60 optional)
Printing plate size :	100 x 250 mm
Max. speed : (dry cycle) *	1,800 / hr.
Pad compression :	1,178N
Pad cylinder :	Ø50 x 125 mm
Power :	110/220V 50/60Hz 65W
Air consumption :	118 litre/min. (approx.)
Accuracy +/- :	0.05 mm
Size : (L x W x H)	893 x 610 x 1,400 mm
Weight :	107 kg (approx.)

* Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.

